## **ART**GUARDIAN®

## Datasheet

## **SENSOR UNIT**

CHOOK OITH	
Color	white
Dimensions	118 x 81 x 11 mm
Weight	ca. 100 g
Components	3 components   Sensor Module, Battery Module, Mounting Adaptor
Included in Delivery	Sensor Module, Battery Module, Mounting Adaptor, Getting Started manual
Power Supply	Battery Module, replaceable
Life of Battery	2 years
Communication	2.4 GHz, encrypted data transfer
Range	ca. 15 meters *
Measure Interval	configurable, minimum 5 minutes, maximum 24 hours
Logger Operation	up to 2 months
Measurands	relative humidity, temperature, acceleration (movement / shock)
Relative Humidity	range 0 100 %   resolution 0.04 %   accuracy typ.: ±1.8 %, max.: ±2.0 % (10 90 %)
Temperature	range -40 $125^{\circ}\mathrm{C}$   resolution $0.01^{\circ}\mathrm{C}$   accuracy $\pm0.2^{\circ}\mathrm{C}$
Acceleration (threshold)	range ±8 g   resolution 6 mg, threshold configurable
Options	up to 2 sensor extensions for additional measurands possible
Environmental Conditions	continuous operation -20 60 °C at 10 90 % R.H., non-condensing   storage 0 35 °C

## **BASE STATION**

Color	white
Dimensions	$80 \times 80 \times 32$ mm (without wall power supply)
Weight	ca. 120 g
Components	2 components   Base Station, wall power supply
Included in Delivery	Base Station, wall power supply, Getting Started manual
Power Supply	100240V / $50-60Hz$ with optional international adaptor plugs
Power Reserve	up to 30 h without mains voltage
Communication	2.4 GHz short-range communication with sensors, GSM (2G) connection
Max. Number of Sensors	max. 6 per base station
Environmental Conditions	continuous operation -20 60 °C at 10 90 % R.H., non-condensing $\mid$ storage 0 35 °C

www.artguardian.com